

1		2		3		4		5		6																																																																																																
						WJH4J-XXP-1Y-00A		<table border="1"><thead><tr><th colspan="7">REVISION RECORD</th></tr><tr><th>REV.</th><th colspan="3">ESCRPTION</th><th>ECN No.</th><th>APPROVED</th><th>DATE</th></tr></thead><tbody><tr><td>V0</td><td colspan="3">新发行</td><td></td><td>YuCZ</td><td>26.04.15</td></tr></tbody></table>				REVISION RECORD							REV.	ESCRPTION			ECN No.	APPROVED	DATE	V0	新发行				YuCZ	26.04.15																																																																										
REVISION RECORD																																																																																																										
REV.	ESCRPTION			ECN No.	APPROVED	DATE																																																																																																				
V0	新发行				YuCZ	26.04.15																																																																																																				
								<table border="1"><thead><tr><th colspan="2">UL/CUL 技术参数</th><th colspan="3">UL1059</th></tr><tr><th>等 级</th><th>Use Group</th><th>B</th><th>C</th><th>D</th></tr></thead><tbody><tr><td>额定电压</td><td>Rated Voltage [V]</td><td>300</td><td>300</td><td>300</td></tr><tr><td>额定电流</td><td>Rated Current [A]</td><td>30</td><td>30</td><td>10</td></tr><tr><td>接线范围</td><td>Wire Range</td><td colspan="3">30-10</td></tr><tr><td>单/多芯线</td><td>Solid/Stranded [AWG]</td><td colspan="3"></td></tr><tr><td>耐电压</td><td>Withstanding Voltage</td><td colspan="3">1600V/1Min</td></tr></tbody></table>				UL/CUL 技术参数		UL1059			等 级	Use Group	B	C	D	额定电压	Rated Voltage [V]	300	300	300	额定电流	Rated Current [A]	30	30	10	接线范围	Wire Range	30-10			单/多芯线	Solid/Stranded [AWG]				耐电压	Withstanding Voltage	1600V/1Min																																																														
UL/CUL 技术参数		UL1059																																																																																																								
等 级	Use Group	B	C	D																																																																																																						
额定电压	Rated Voltage [V]	300	300	300																																																																																																						
额定电流	Rated Current [A]	30	30	10																																																																																																						
接线范围	Wire Range	30-10																																																																																																								
单/多芯线	Solid/Stranded [AWG]																																																																																																									
耐电压	Withstanding Voltage	1600V/1Min																																																																																																								
WJH4K-01P-1Y-00A								<table border="1"><thead><tr><th colspan="2">IEC 技术参数</th><th colspan="3">IEC61984</th></tr><tr><th>过电压类别</th><td>Overvoltage Category</td><td>III</td><td>III</td><td>II</td></tr><tr><td>污染等级</td><td>Contamination Class</td><td>3</td><td>2</td><td>2</td></tr><tr><td>额定电压</td><td>Rated Voltage [V]</td><td>400</td><td>400</td><td>/</td></tr><tr><td>额定电流</td><td>Rated Current [A]</td><td>41</td><td>41</td><td>/</td></tr><tr><td>额定冲击电压</td><td>Impulse withstand voltage [KV]</td><td>6.0</td><td>6.0</td><td>/</td></tr><tr><td>导线截面积</td><td>Conductor cross section</td><td colspan="3">0.2-6.0</td></tr><tr><td>硬质/柔性导线</td><td>Solid/flexible [mm²]</td><td colspan="3"></td></tr><tr><td>材 料</td><td>Material</td><td colspan="3"></td></tr><tr><td>绝缘材料</td><td>Insulation Material</td><td colspan="3">PA66</td></tr><tr><td>阻燃等级</td><td>Imflammability</td><td colspan="3">UL94V-0</td></tr><tr><td>导体材料</td><td>Contactur Material</td><td colspan="3">铜合金 Copper alloy</td></tr><tr><td>导体表面镀层</td><td>Contactive Coating</td><td colspan="3">镀锡 Sn Plated</td></tr><tr><td colspan="5">一般参数 Other Data</td></tr><tr><td>间距 Pitch /极数 Poles</td><td>[mm] / [P]</td><td colspan="3">8.10/XX=01P</td></tr><tr><td>剥线长度 Stripping Length</td><td>[mm]</td><td colspan="3">9</td></tr><tr><td>螺丝 Screw/扭矩 Torque(Max)</td><td>[N.m]</td><td colspan="3">M3/0.5</td></tr><tr><td>工作温度 Operating temperature</td><td>[°C]</td><td colspan="3">-40~105</td></tr><tr><td colspan="5">符合RoHS环保要求</td></tr></thead></table>				IEC 技术参数		IEC61984			过电压类别	Overvoltage Category	III	III	II	污染等级	Contamination Class	3	2	2	额定电压	Rated Voltage [V]	400	400	/	额定电流	Rated Current [A]	41	41	/	额定冲击电压	Impulse withstand voltage [KV]	6.0	6.0	/	导线截面积	Conductor cross section	0.2-6.0			硬质/柔性导线	Solid/flexible [mm²]				材 料	Material				绝缘材料	Insulation Material	PA66			阻燃等级	Imflammability	UL94V-0			导体材料	Contactur Material	铜合金 Copper alloy			导体表面镀层	Contactive Coating	镀锡 Sn Plated			一般参数 Other Data					间距 Pitch /极数 Poles	[mm] / [P]	8.10/XX=01P			剥线长度 Stripping Length	[mm]	9			螺丝 Screw/扭矩 Torque(Max)	[N.m]	M3/0.5			工作温度 Operating temperature	[°C]	-40~105			符合RoHS环保要求				
IEC 技术参数		IEC61984																																																																																																								
过电压类别	Overvoltage Category	III	III	II																																																																																																						
污染等级	Contamination Class	3	2	2																																																																																																						
额定电压	Rated Voltage [V]	400	400	/																																																																																																						
额定电流	Rated Current [A]	41	41	/																																																																																																						
额定冲击电压	Impulse withstand voltage [KV]	6.0	6.0	/																																																																																																						
导线截面积	Conductor cross section	0.2-6.0																																																																																																								
硬质/柔性导线	Solid/flexible [mm²]																																																																																																									
材 料	Material																																																																																																									
绝缘材料	Insulation Material	PA66																																																																																																								
阻燃等级	Imflammability	UL94V-0																																																																																																								
导体材料	Contactur Material	铜合金 Copper alloy																																																																																																								
导体表面镀层	Contactive Coating	镀锡 Sn Plated																																																																																																								
一般参数 Other Data																																																																																																										
间距 Pitch /极数 Poles	[mm] / [P]	8.10/XX=01P																																																																																																								
剥线长度 Stripping Length	[mm]	9																																																																																																								
螺丝 Screw/扭矩 Torque(Max)	[N.m]	M3/0.5																																																																																																								
工作温度 Operating temperature	[°C]	-40~105																																																																																																								
符合RoHS环保要求																																																																																																										

	General Tolerances								— ▯ ⊥				--------------------	-------	--------------	---------------	---------------	----------------	-----------------	-------------	-------	----------------	-------------		variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to		tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60										5	Screw	Steel	Zn Plated		------	------------------	--------------	-----------		4	Conductive board	Copper Alloy	Sn Plated		3	Cage	Copper Alloy	Ni Plated		2	Housing-K	PA66	UL94V-0		1	Housing-J	PA66	UL94V-0		ITEM	NAME OF PART	MATERIAL	NOTES				
									DES.	YuCZ	DATE	26.04.15	UNITS	mm	THIRD ANGLE PROJECTION				--	--------	------	----------	-------	-----	------------------------	------------------------------	----		CHK.	YangHJ	DATE	26.04.15	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1			APP.	JASON	DATE	26.04.15	SCALE	5:6	DRAWING TYPE: SP-03	REV	V0		慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD							PART NO.: WJH4-XXP-1Y-00A																																						
1		2		3		4		5		FOR-0371 Rev.1.0																																																																																				

D